



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	25-0100-5	<b>Version Number:</b>	5.00
<b>Issue Date:</b>	05/22/18	<b>Supersedes Date:</b>	12/11/17

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Sandblast Filler 3

#### Product Identification Numbers

70-9020-1262-7

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Filler, Industrial use

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Liquid: Category 2.  
Skin Corrosion/Irritation: Category 2.  
Reproductive Toxicity: Category 2.  
Carcinogenicity: Category 2.  
Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Flame | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Highly flammable liquid and vapor.

Causes skin irritation.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Suspected of causing cancer.

**Precautionary Statements****Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Solvent Naphtha (Petroleum), Light Aliphatic	64742-89-8	60 - 100
Polyisoprene	9003-31-0	10 - 30
Ethyl Alcohol	64-17-5	1 - 5

Heptane	142-82-5	0.5 - 5.0
2,5-di-tert-Amylhydroquinone	79-74-3	0.1 - 1
Methyl Alcohol	67-56-1	0.1 - 1
Titanium Dioxide	13463-67-7	0.1 - 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide

Carbon dioxide

#### Condition

During Combustion

During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors

in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Heptane	142-82-5	OSHA	TWA:2000 mg/m3(500 ppm)	
Ethyl Alcohol	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcin.
Ethyl Alcohol	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	
Methyl Alcohol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	SKIN
Methyl Alcohol	67-56-1	OSHA	TWA:260 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Butyl Rubber

Fluoroelastomer

Polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Viscous
<b>Odor, Color, Grade:</b>	hydrocarbon odor, clear to light yellow in color
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	>=93 °C
<b>Flash Point</b>	16 °F [ <i>Test Method:</i> Closed Cup]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	1.1 % volume
<b>Flammable Limits(UEL)</b>	7.0 % volume
<b>Vapor Pressure</b>	<=40 mmHg [ <i>@</i> 68 °F]
<b>Vapor Density</b>	3.50 [ <i>Ref Std:</i> AIR=1]
<b>Density</b>	0.70 g/ml

Specific Gravity	0.70 [ <i>Ref Std: WATER=1</i> ]
Solubility in Water	Slight (less than 10%)
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	480 °C [ <i>Details: Toluene</i> ]
Decomposition temperature	<i>No Data Available</i>
Viscosity	10,000 - 15,000 centipoise [ <i>@ 73.4 °F</i> ] [ <i>Test Method: Brookfield</i> ]
Hazardous Air Pollutants	<=0.8 % weight [ <i>Test Method: Calculated</i> ]
Volatile Organic Compounds	636 g/l [ <i>Details: EU VOC content</i> ]
Percent volatile	Approximately 80 % weight [ <i>Test Method: Estimated</i> ]
VOC Less H2O & Exempt Solvents	638 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. May cause additional health effects (see below).

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Additional Information:**

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Solvent Naphtha (Petroleum), Light Aliphatic	Dermal	Rabbit	LD50 3,000 mg/kg
Solvent Naphtha (Petroleum), Light Aliphatic	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Solvent Naphtha (Petroleum), Light Aliphatic	Ingestion	Rat	LD50 > 5,000 mg/kg
Polyisoprene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyisoprene	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Heptane	Dermal	Rabbit	LD50 3,000 mg/kg

Heptane	Inhalation-Vapor (4 hours)	Rat	LC50 103 mg/l
Heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
Ethyl Alcohol	Dermal	Rabbit	LD50 > 15,800 mg/kg
Ethyl Alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 124.7 mg/l
Ethyl Alcohol	Ingestion	Rat	LD50 17,800 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Methyl Alcohol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methyl Alcohol	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
Methyl Alcohol	Ingestion		LD50 estimated to be 50 - 300 mg/kg
2,5-di-tert-Amylhydroquinone	Dermal	Rabbit	LD50 > 3,160 mg/kg
2,5-di-tert-Amylhydroquinone	Ingestion	Rat	LD50 1,900 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Solvent Naphtha (Petroleum), Light Aliphatic	Rabbit	Irritant
Polyisoprene	Professional judgement	No significant irritation
Heptane	Human	Mild irritant
Ethyl Alcohol	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Methyl Alcohol	Rabbit	Mild irritant
2,5-di-tert-Amylhydroquinone	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Solvent Naphtha (Petroleum), Light Aliphatic	Rabbit	No significant irritation
Polyisoprene	Professional judgement	No significant irritation
Heptane	Professional judgement	Moderate irritant
Ethyl Alcohol	Rabbit	Severe irritant
Titanium Dioxide	Rabbit	No significant irritation
Methyl Alcohol	Rabbit	Moderate irritant
2,5-di-tert-Amylhydroquinone	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
Polyisoprene	Human	Not classified
Ethyl Alcohol	Human	Not classified
Titanium Dioxide	Human and animal	Not classified
Methyl Alcohol	Guinea pig	Not classified
2,5-di-tert-Amylhydroquinone	Human	Not classified



**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Solvent Naphtha (Petroleum), Light Aliphatic	In Vitro	Not mutagenic
Heptane	In Vitro	Not mutagenic
Ethyl Alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethyl Alcohol	In vivo	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Methyl Alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Solvent Naphtha (Petroleum), Light Aliphatic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethyl Alcohol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Methyl Alcohol	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Ethyl Alcohol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
Ethyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	prematuring & during gestation
Methyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
Methyl Alcohol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
Methyl Alcohol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Solvent Naphtha (Petroleum), Light Aliphatic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Solvent Naphtha	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	

(Petroleum), Light Aliphatic			data are not sufficient for classification		available	
Solvent Naphtha (Petroleum), Light Aliphatic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
Ethyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
Ethyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
Ethyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
Methyl Alcohol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methyl Alcohol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Heptane	Inhalation	liver   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks
Ethyl Alcohol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
Ethyl Alcohol	Inhalation	hematopoietic system   immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
Ethyl Alcohol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
Ethyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Alcohol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
Methyl Alcohol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
Methyl Alcohol	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
Solvent Naphtha (Petroleum), Light Aliphatic	Aspiration hazard
Heptane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

**Health Hazards**

Carcinogenicity

Reproductive toxicity

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health: 2 Flammability: 3 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	25-0100-5	<b>Version Number:</b>	5.00
<b>Issue Date:</b>	05/22/18	<b>Supersedes Date:</b>	12/11/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**