

May, 2007

3M™ Sandblast Stencil 510

Product Description

3M™ Sandblast Stencil 510, also known as letter perfect, can be used for hand-cut and die-cut applications as a surface protection during blasting procedures.

Product Features

- Takes distinct carbon transfer.
- Easy to cut and lines show up clearly.
- Excellent blast resistance.
- One piece removal.
- Excellent adhesion to many polished surfaces.



3M™ Sandblast Stencil 510

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Total Tape Thickness	1.4 mm	45 mil	ASTM D3652
Backing	Light green colored rubber		
Adhesive	Rubber		
Liner	Polyester		
Liner Thickness	0.05 mm	2 mil	

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	3.3 N/cm	30 oz/in	ASTM D3330	Granite

Available Sizes

Standard Roll Sizes

123/4 in, 183/4 in, 25 in x 10 yd (9 m)

Handling/Application Information

Application Ideas

- Can be used to help protect granite, marble and wood during sandblasting operations:
 - a. Designed for single-process technique and straight blasting.
 - b. Used for two-process shape carving.
- Excellent for wood sign sandblasting.
- Can be used for gaskets, cushioning and other applications where heavy, uniform caliper is desired.

3M™ Sandblast Stencil 510

Handling/Application Information (continued)

Application Techniques

- It is recommended that this stencil not be applied to cold stone because of possible condensation forming on the surface when placed in warm areas and should be applied to a warm, clean and dry surface.
- To minimize shrinkage, allow rubber backing to relax before applying to the stone. Rub down firmly to adhere stencil to the stone. Use 3M™ Sandblast Filler #2 to help increase adhesion and hold stencil to polish stone surfaces.
- Can be die-cut by reversing the liner so that the non-treated side of the liner is against the adhesive.

Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton. To obtain best performance, use this product within 12 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/~/~3M-Sandblast-Stencil-Hand-Cut-Splice-Free-510?N=5002385+3293241718&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=510

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Sandblast Stencil 510

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M™ Sandblast Stencil 510



3M United States
3M Center
St. Paul, MN 55144-1000
800-362-3550
www.3M.com

Please recycle.
© 3M 2020. All Rights Reserved.

The brands listed above are trademarks of 3M