

November, 2018

3M™ Scotch® Transparent Film Tape 600

Product Description

Scotch® Tape 600 is a transparent film tape that is excellent for various packaging applications. It has a pressure sensitive acrylic adhesive system which is long aging and highly transparent. The combination of this adhesive and the backer gives this tape excellent stain and sunlight resistance, making it an excellent choice for use on fabrics. Scotch® Tape 600 is also recommended for gift-wrapping, combining, attaching, light duty carton sealing and other miscellaneous uses.

Product Features

- Easy-release treated.
- Meets CID A-A-113 Type 1 Class D.
- Moisture and chemical resistant.
- Roll stability.
- Long aging.
- Controlled, smooth unwind.
- Unaffected by changing atmospheric conditions and resistant to many acids, alkalies and solvents.
- Has good edge tear and breakage resistance.
- Easy to read through.
- Excellent holding and good dispensing properties.
- Does not yellow on fabrics.



3M™ Scotch® Transparent Film Tape 600

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Transparent		
Total Tape Thickness	0.058 mm	2.3 mil	ASTM D3652
Backing Thickness	0.038 mm	1.5 mil	ASTM D3652
Backing	3M™ UPVC Film		
Adhesive	Pressure sensitive acrylic		

Typical Performance Characteristics

Property	Values		Method	Substrate	Test Condition
Peel Adhesion	3.5 N/cm	32 oz/in	ASTM D3330	Stainless Steel	
Tensile Strength	49 N/cm	28 lb/in	ASTM D3759		Machine Direction
Elongation at Break	45 %		ASTM D3759		

Available Sizes

Property	Values	
Standard Roll Length	66 m	72 yd

Table continued on next page

3M™ Scotch® Transparent Film Tape 600

Available Sizes (continued)

Property	Values	
Standard Width	9.5, 12.7, 19, 25.4, 38.1, 50.8 mm	3/8, 1/2, 3/4, 1, 1.5, 2 in
Core Size (ID)	76.2 mm	3 in
Available Sizes	Custom widths and lengths available on request, subject to minimum order requirements.	

Handling/Application Information

Application Techniques

An extensive line of manual, semi-automatic and automatic equipment is available to facilitate application of Scotch® Tape 600.

Storage and Shelf Life

Storage of Scotch® Tape 600 at 70°F (21°C) and 40-50% relative humidity is recommended. To obtain best performance, use this product within 18 months from date of manufacture.

Industry Specifications

Meets CID A-A-113 Type 1 Class A

Trademarks

Scotch is a registered trademark of 3M Company.
3M is a trademark of 3M Company.

3M™ Scotch® Transparent Film Tape 600

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/search/~/Scotch-Light-Duty-Packaging-Tape-600-High-Clarity?N=5002385+3293242421&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=600

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Scotch® Transparent Film Tape 600

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M™ Scotch® Transparent Film Tape 600



3M United States
3M Center
St. Paul, MN 55144-1000
800-362-3550
www.3M.com

Please recycle.
© 3M 2020. All Rights Reserved.

The brands listed above are trademarks of 3M